

## PRODUCT INFORMATION SHEET

### Timberline® Natural Shadow®

#### Shingles

*Value & Performance In A Natural Wood-Shake Look*



## PRODUCT INFORMATION

*"Protect your home with Timberline® Shingles — North America's #1-selling shingles!"*

### Timberline® Natural Shadow® Shingles Provide These Unique Benefits:

- **Great Value . . .** Architecturally stylish but practically priced—with a Lifetime Ltd. warranty.<sup>1</sup>
- **Attractive Appearance . . .** Features a classic shadow effect. Lends any home a subtle, even-toned look with the warmth of wood.
- **Highest Fire Rating . . .** Class A fire rating from Underwriters Laboratories.
- **High Performance . . .** Designed with Advanced Protection® Shingle Technology, which reduces the use of natural resources while providing excellent protection for your home (visit [gaf.com/aps](http://gaf.com/aps) to learn more).
- **Stays In Place . . .** Dura Grip™ Adhesive seals each shingle tightly and reduces the risk of shingle blow-off. Shingles warranted to withstand winds up to 130 mph!<sup>2</sup>
- **Peace Of Mind . . .** Lifetime Ltd. transferable warranty with Smart Choice® Protection (non-prorated material and installation labor coverage) for the first ten years.<sup>1</sup>
- **Perfect Finishing Touch . . .** Use Timbertex® Premium Ridge Cap Shingles or Ridglass® Premium Ridge Cap Shingles.<sup>3</sup>

<sup>1</sup>See *GAF Shingle & Accessory Ltd. Warranty* for complete coverage and restrictions. The word "Lifetime" refers to the length of coverage provided by the *GAF Shingle & Accessory Ltd. Warranty* and means as long as the original individual owner(s) of a single-family detached residence [or the second owner(s) in certain circumstances] owns the property where the shingles are installed. For owners/structures not meeting the above criteria, Lifetime coverage is not applicable.

<sup>2</sup>This wind speed coverage requires special installation; see *GAF Shingle & Accessory Ltd. Warranty* for details.

<sup>3</sup>These products are not available in all areas. See [www.gaf.com/ridgecapavailability](http://www.gaf.com/ridgecapavailability) for details.

## COLORS/AVAILABILITY

- **COLORS:** Arctic White, Barkwood, Birchwood, Charcoal, Driftwood, Hickory, Hunter Green, Pewter Gray, Shakewood, Slate, Weathered Wood
- **REGIONAL AVAILABILITY:**\* Northeast, Southeast, Southwest, West, and Central Areas

\*See [http://www.gaf.com/Roofing/Residential/Products/Shingles/Timberline/Natural\\_Shadow](http://www.gaf.com/Roofing/Residential/Products/Shingles/Timberline/Natural_Shadow) for color availability in your area

## APPLICABLE STANDARDS & PROTOCOLS

- UL 790, Class A
- Miami-Dade County Product Control Approved – 13-0419.04 (Available in Southeast; contact Technical Services at 800.766.3411)
- Florida Building Code Approved FL10124-R12
- UL 997 modified to 110 mph
- ASTM D7158, Class H
- ASTM D3161, Class F
- ASTM D3018, Type 1
- ASTM D3462
- ICC ESR-1475, ESR-3267\*\*
- Texas Department of Insurance
- ENERGY STAR® qualified (U.S. only; Arctic White only)

Effective 7/1/08, existing NYC MEA's may be used but are no longer required.

\*\*Obtained ESR 3267 evaluation from ICC Evaluation Services based on compliance with the requirements of AC438, an acceptance criteria established by ICC Evaluation Services to evaluate asphalt shingles that contains performance tests in addition to those required by the building code. (ICC Evaluation Services provides technical evaluations of building products that directly address the issue of code compliance. Building inspectors use these evaluation reports to help determine code compliance and enforce building regulations.)

## PRODUCT/SYSTEM SPECIFICS†

- Fiberglass Asphalt Construction
- Dimensions (approx.): 13 1/4" x 39 3/8" (336.5 x 1001.1 mm)
- Exposure: 5 5/8" (142.88 mm)
- Bundles/Square: 3
- Pieces/Square: 64
- Nails/Square: 256 (384 where 6 nails per shingle is required)††
- StainGuard® Protection: Yes (Location dependent; contact Technical Services at 800.766.3411)
- Hip/Ridge: Timbertex®; Seal-A-Ridge®; Z®Ridge; Ridglass®
- Starter: ProStart™; WeatherBlocker™

†Refer to complete published installation instructions.

††Required by some local codes and required for enhanced wind coverage on certain products.

## INSTALLATION

Detailed installation instructions are provided on the inside of each bundle wrapper of Timberline® Natural Shadow® Shingles. Installation instructions may also be obtained at [www.gaf.com](http://www.gaf.com).